
# **AFL** HYPERSCALE.

# OM2 Simplex/Duplex Enhanced Patch Cord



### Description

Multimode enhanced patch cords are used to connect high speed and legacy networks like gigabit ethernet, fast ethernet and ethernet. Multimode patch cords are manufactured for internal use using LSZH cable and conform to IEC, EIA TIA or Telcordia standards. OM2 patch cords are terminated with optimized connectors giving optimum optical performance.

#### Features and Benefits

- FC, LC, MTRJ, SC and ST connectors
- 900 μm / 600 μm tight buffer
- Simplex and duplex assembly options
- Higher optical performance available on request
- REACH, RoHS & SvHC materials compliant

- Low smoke zero halogen (LSZH) cable in orange color
- OM2 fiber conforms to ITU-T G.651.1, TIA/EIA 492AAAB, IEC60793-2-10 A1a.1a
- SC and LC duplex assemblies available with clips
- Armoured option also available











# **AFL** HYPERSCALE.

# **Applications**

- For use in 1 Gb/s high speed LAN networks over a 550 m indicative link length at 850 nm wavelength using a laser launch
- Data centers
- Supports video, data and voice services

- High speed and legacy networks including Gigabit Ethernet, Fast Ethernet and Ethernet
- Premises cabling in data networks including backbone, riser and horizontal

# **Specifications**

### **Connector Specification**

OPTICAL PERFORMANCE	MULTIMODE	CONFORMANCE
IL Max/Master (Acceptance)*	0.25 dB	IEC 61300-3-4
Ave/Master	0.15 dB	IEC 61300-3-4

Note: Return Loss ≥28 dB based on sample data using method IEC 61300-3-6

### Cable Specification

CHARACTERISTICS	
Cable Material	LSZH
Strength Member	Aramid
Crush (N)	1000
Operating Temperature (°C)	-20 to 60
Fire Specification	IEC 60332-1

# Fiber Specification

CHARACTERISTICS				
Attenuation (dB / km)	2.8 @ 850 nm / 0.8 @ 1300 nm			
Bandwidth OFL (MHz x km)	500 @ 850 nm / 500 @ 1300 nm			

# **Ordering Information**

Code	Cable Type		Code	End A		End B		Code			Unit	Length	
P2	AH1	Simplex 2mm	L2E	Α	LC	Α	LC		-0000-	М	Meters	1	1
	AK1	Simplex 3mm		D	SC	D	SC			F	Feet	2	2
	AQ2	ZIP 2mm		Н	FC	Н	FC					3	3
	AT2	ZIP 3mm		K	ST	K	ST					5	5
	AU2	Flat 2mm		N	MTRJ F*	N	MTRJ F*					10	10
	AV2	Flat 2.8mm		Р	MTRJ M*	Р	MTRJ M*					XX	Specify











# Legacy ordering information

	ector d A		nector d B	M	lode	Cable Configuration		Cable Colour		Cable Length		
FC	FC	FC	FC	50	OM2	S	Simplex	OR	Orange	1	1 metre	
LC	LC	LC	LC			D	Duplex			2	2 metre	
MTRJ	MTRJ	MTRJ	MTRJ			FD	Flat Duplex			3	3 metre	
SC	SC	SC	SC							5	5 metre	
ST	ST	ST	ST							10	10 metre	
										XX	Specify	

<sup>\*</sup> MTRJ is only available in MiniZip duplex, insertion loss  $\leq$  0.5 dB

#### **Example Part Number**

L	_C	SC	50	D	OR	3
---	----	----	----	---	----	---

This part number has created a 3 metre duplex LC to SC OM2 LSZH patch cord in orange.

#### **Related Products**















