



## 5-Port Gigabit GREENnet Switch TEG-S5g (V1.0R)

The compact 5-Port Gigabit GREENnet Switch provides high bandwidth performance, ease of use and reliability, all while reducing power consumption by up to 70%.

GREENnet technology automatically adjusts power voltage as needed, resulting in substantial energy savings.

Boost your office efficiency and eliminate network congestion with Gigabit speeds and total switching capacity of 10Gbps with Full-Duplex Mode. Plug and Play this sturdy metal switch for reliable high-speed network connectivity.

### FEATURES • 5 x 10/100/1000Mbps Auto-Negotiation, Auto-MDIX Gigabit Ethernet ports

- Store-and-Forward switching architecture with non-blocking wire-speed performance
- IEEE 802.3x Flow Control for full-duplex mode
- Back pressure Flow Control for half-duplex mode
- Integrated address look-up engine with 1K absolute MAC address table and 104KBytes RAM data buffering
- Operates and maximizes packet filtering and forwarding rate
- Jumbo Frame support up to 9612Bytes
- Diagnostic LEDs and Plug & Play
- 3 year limited warranty

# 5-Port Gigabit GREENnet Switch


TEG-S5g (V1.0R)

## SPECIFICATIONS

Hardware	
Standards	<ul style="list-style-type: none"><li>• IEEE 802.3 10Base-T; IEEE 802.3u 100Base-TX</li><li>• IEEE 802.3ab 1000Base-T; IEEE 802.3x Flow Control</li></ul>
Network Media	<ul style="list-style-type: none"><li>• Ethernet: Cat. 3,4,5, up to 100m</li><li>• Fast Ethernet: Cat. 5, up to 100m</li><li>• Gigabit Ethernet: Cat. 5, 5e,6, up to 100m</li></ul>
Data Rate	<ul style="list-style-type: none"><li>• Ethernet: 10Mbps/20Mbps (half/full-duplex)</li><li>• Fast Ethernet: 100Mbps/200Mbps (half/full-duplex)</li><li>• Gigabit Ethernet: 2000Mbps (full-duplex)</li></ul>
Protocol / Topology	<ul style="list-style-type: none"><li>• CSMA/CD, Star</li></ul>
Power Consumption	<ul style="list-style-type: none"><li>• 3w (max)</li></ul>
Switch Fabric	<ul style="list-style-type: none"><li>• 10Gbps forwarding capacity</li></ul>
Interface	<ul style="list-style-type: none"><li>• 5 x 10/100/1000Mbps Auto-MDIX RJ-45 ports</li></ul>
Data RAM Buffer	<ul style="list-style-type: none"><li>• 104KBytes</li></ul>
Filtering Table	<ul style="list-style-type: none"><li>• 1K entries</li></ul>
Diagnostic LED	<ul style="list-style-type: none"><li>• Power, Link/ACT, 100Mbps, 1000Mbps</li></ul>
Power Adapter	<ul style="list-style-type: none"><li>• 5V DC, 2.5A external power adapter</li></ul>
Dimension	<ul style="list-style-type: none"><li>• 150 x 105 x 33mm (5.9x 4.1 x 1.3 in)</li></ul>
Weight	<ul style="list-style-type: none"><li>• 225g (8oz)</li></ul>
Temperature	<ul style="list-style-type: none"><li>• 0° ~ 50° C (32° ~ 122° F)</li></ul>
Humidity	<ul style="list-style-type: none"><li>• 10%~90% (non-condensing)</li></ul>
Certifications	<ul style="list-style-type: none"><li>• FCC, CE</li></ul>

\*Max power savings compared with standard TRENDnet switches.

## NETWORKING SOLUTIONS



## PACKAGE CONTENTS

- TEG-S5g
- Multi-Language Quick Installation Guide
- Power Adapter

## RELATED PRODUCTS

TEG-S80g	8-Port Gigabit GREENnet Switch
TEG-PCBUSR	10/100/1000Mbps Gigabit CardBus PC Card
TEG-PCITXR	10/100/1000Mbps Gigabit PCI Adapter

## ORDERING INFORMATION

**TRENDnet**

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: [www.trendnet.com](http://www.trendnet.com)

Email: [sales@trendnet.com](mailto:sales@trendnet.com)

To Order Please Call:

**1-888-326-6061**

