



## Product information

# Weller®

### WXR 3030 Set

Code No. : T0053501699

#### Rework station

WXR 3 Power unit with WXHAP 200 Hot-air iron (200 W/24 V), WXDP 120 Desoldering iron for horizontal use (120 W/24 V), WXP 65 Soldering iron (65 W/24 V), WVP Vacuum Pick-Up, PDN Pliers Desoldering Nozzle, WDH 30, WDH 70, WDH 10 Safety rests

#### Technical Data



This station is ESD safe.

<b>Dimensions L x W x H:</b>	273 x 235 x 102 mm (10,75 x 9,25 x 4,02 inch)
<b>Weight:</b>	ca. 6,7 kg
<b>Mains supply voltage:</b>	230 V, 50 Hz / 120 V, 60 Hz / 100 V 50/60 Hz
<b>Power consumption:</b>	420 W (600 W)
<b>Safety class:</b>	I, antistatic housing III, soldering tool
<b>Fuse:</b>	Overcurrent release 230 V; 2,0 A 120 V; 4,0 A
<b>Temperature accuracy:</b>	± 9°C (± 17°F) depends on tool (WXHAP ± 30°C / ±80°F)
<b>Temperature stability:</b>	± 2°C (± 4°F)
<b>Equipotential bonding:</b>	Via 3.5 mm pawl socket on back of unit
<b>Display:</b>	240 x 88 dots / Backlighting
<b>USB-Schnittstelle:</b>	The control unit comes with a USB port for installing firmware updates, configuration and monitoring.

**Built in pump:** (Intermittent operation 30/30 s)  
Max. vacuum: 0,7 bar  
Max. flow: 18l/min  
Hot air max. 15 l/min

---

**Additional vacuum pump:** Max. vacuum: 0,7 bar  
Max. flow: 18l/min

---

Weller®