



### CSB12 FTTH Customer Outlet SC Duplex / LC Quad



The internal customer outlet box is designed for use inside the home. The operator has the choice to have the box unloaded or equipped with adaptors, the box is designed with integrated shutters to comply with safety standards.

#### FEATURES

- Multiple cable entry points
- Integrated heatshrink splice holder
- Hinged splice Tray
- Holds up to 4 single fibres 1 x SC Duplex or 1 x LC Quad
- Integrated fibre management
- Integrated shutter protects against laser exposure and dust

#### APPLICATIONS

- FTTH

#### SPECIFICATION

PRODUCT SPECIFICATION	VALUE
Maximum Single Fibre Count	4
Maximum Number of heat splice	4
Number of cable entre points	4
Height	86mm
Width	116mm
Depth	23mm
Colour	White
Material	ABS
Flame Retardant	Yes
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN 50173, IEC 60304, IEC 61754, EN 297-1

#### ORDERING INFORMATION

##### DESCRIPTION

FTTH User outlet unloaded CSB12

#### CONTACT OUR SALES TEAM TODAY

**Europe:** +44 1908 441 100 | [sales@optronicsnet.com](mailto:sales@optronicsnet.com)

**Americas:** +1 800 790 9932 | [sales@optronicsnet.com](mailto:sales@optronicsnet.com)  
**Asia Pacific:** +86 755 2561 3694 | [apac@optronicsnet.com](mailto:apac@optronicsnet.com)  
**Middle East & Africa:** +971 4 404 9606 | [mea@optronicsnet.com](mailto:mea@optronicsnet.com)  
**Web:** [www.optronicsnet.com](http://www.optronicsnet.com)

Downloaded from [www.optronicsnet.com](http://www.optronicsnet.com) | Information correct as of November 6, 2015 | Optronics reserves the right to make changes to the product specifications in this datasheet at any time without notice.  
All content © Optronics 2017