

5m HDMI to DVI-D Cable, Gold Line

Part No.: 36197



Description

- Advanced, high performance HDMI to DVI-D cables with gold design connector
- Supports DVI resolutions up to 1920x1200@60Hz and HDTV resolutions up to 1080p
- Advanced low attenuation design with 24K gold plated contacts for signal integrity and long distance transmission
- Metal connector greatly reduces interference and provides increased EMC shielding without the need for a ferrite core
- 25 Year Warranty

From the Lines cable connectivity concept developed by Lindy, Gold Line HDMI to DVI-D cables are the no compromise, high performance connection solution for use in the most demanding professional environments

These superior quality cables utilise a unique low attenuation design that ensures consistent and reliable transmission even over very long distances.

For complete signal integrity, Gold Line HDMI to DVI-D cables feature 24K gold plated contacts, triple shielding with 100% aluminium mylar wrap and an 85% tinned copper braid.

Gold Line HDMI to DVI-D cables support DVI resolutions up to 1920x1200@60Hz including HD resolutions up to 1080p.

Gold Line HDMI to DVI-D cables are available in 0.5m, 1m, 2m, 3m, 5m, 10m, and 15m lengths.

Technical details

Connectors:

- Connector A: HDMI Typ A Male
- Connector B: DVI-D Male (Single Link)
- Housing Material: 24K Gold Plated Metal
- Connector Plating: 24K Gold 3µm
- Pin Construction: Phosphor Bronze
- Pin Plating: 24K Gold 15µm
- Dimensions (approx.) WxDxH: HDMI: 20x11.2x36mm (0.78x0.44x1.42in), DVI:39.5x16.5x44.5mm

(1.55x0.65x1.73in)

Cable Construction:

- Length: 5m (16.40ft)
- Standard: DVI-D Single Link
- Colour: Grey
- Type: Round
- Jack Diameter: 9mm (0.35in)
- Jacket Material: PVC
- Conductor Material: OFC Copper
- Conductor Gauge: 24AWG
- Shielding: Copper Braid 85%

Specifications:

- Supported Bandwidth: 4.95 Gbps
- Maximum Resolution: 1920x1200@60Hz
- Nominal Attenuation: 1 - 825Mhz < 8db
- Minimum Bend Radius: 126mm (4.96in)
- Operating Temperature: -20°C - 80°C (-4°F - 176°F)
- Storage Temperature: -25°C - 85°C (-13°F - 185°F)

Miscellaneous:

- Packaging Type: Polybag
- Warranty (Years): 25
- Certificated: RoHS, REACH, UL

Purchasing Information:

- No. 36197
- EAN: 4002888361972
- This product is also available in other lengths: 36193 - 0.5m (1.64ft), 36194 - 1m (3.28ft), 36195 - 2m (6.56ft), 36196 - 3m (9.84ft), 36198 - 10m (32.81ft), 36199 - 15m (49.21ft)