



# 7.5m DVI-D Dual Link Cable, Gold Line

Part No.: 36205

### Description

- Advanced, high performance DVI-D Dual Link cable with gold design connector
- Supports DVI resolutions up to 2560x1600@60Hz and HD resolutions up to 1080p
- Low attenuation design with 24K gold plated contacts for signal integrity and long distance transmissio
- Metal connector greatly reduces interference and provides increased EMC shielding without the need for a ferrite core
- 25 year warranty

From the Lines cable connectivity concept developed by Lindy, Gold Line DVI-D Dual Link cables are the no compromise, high performance connection solution for use in the most demanding professional environments

These superior quality cables utilise a unique low attenuation design that ensures consistent and reliable transmission even over very long distances.

For complete signal integrity, Gold Line DVI-D Dual Link cables feature 24K gold plated contacts, triple shielding with 100% aluminium mylar wrap and an 85% tinned copper braid.

Gold Line DVI-D Dual Link cables support DVI resolutions up to 2560x1600@60Hz including HD resolutions up to 1080p.

Gold Line DVI-D Dual Link cables are available in 0.5m, 1m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m and 25m lengths.

### **Technical details**

#### **Connectors:**

- Connector A: DVI-D Male (Dual Link)
- Connector B: DVI-D Male (Dual Link)
- Housing Material: 24K Gold Plated Metal
- Connector Plating: 24K Gold 3μm
- Pin Construction: Phosphor Bronze
- Pin Plating: 24K Gold 15μm
- Dimensions (approx.) WxDxH: 39.5x16.5x44.5mm (1.55x0.65x1.73in)

#### **Cable Construction:**

Length: 7.5m (24.61ft)Standard: DVI-D Dual Link

Colour: GreyType: Round

• Jack Diameter: 8.6mm (0.34in)

• Jacket Material: PVC

• Conductor Material: OFC Copper

Conductor Gauge: 28AWGShielding: Copper Braid 85%

## **Specifications:**

• Supported Bandwidth: 9.9 Gbps

Maximum Resolution: 2560x1600@60Hz
Nominal Attenuation: 1 - 825Mhz < 8db</li>
Minimum Bend Radius: 120mm (4.72in)

Operating Temperature: -20°C - 80°C (-4°F - 176°F)
Storage Temperature: -25°C - 85°C (-13°F - 185°F)

### Miscellaneous:

Packaging Type: PolybagWarranty (Years): 25

• Certificated: RoHS, REACH, UL

# **Purchasing Information:**

• No. 36205

• EAN: 4002888362054

• This product is also available in other lengths: 36200 - 0.5m (1.64ft), 36201 - 1m (3.28ft), 36202 - 2m (6.56ft), 36203 - 3m (9.84ft), 36204 - 5m (16.40ft), 36206 - 10m (32.81f)

© LINDY 2017