

0.5m High Speed HDMI Cable, Cromo Line

Part No.: 37870



Description

- High quality Cromo HDMI Cable with 24K gold plated contacts
- Supports UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 8bit
- Supports Dolby® True HD, DTS-HD Master Audio up to 32 audio channels
- 10 year warranty

From the Lines cable connectivity concept developed by Lindy, Cromo Line High Speed HDMI cables are high performance, designer connections that combine premium construction materials with striking connector architecture.

For complete signal integrity, Cromo Line High Speed HDMI cables feature 24K gold plated contacts; triple shielding with 100% aluminium mylar wrap and an 85% tinned copper braid.

Cromo Line cables feature sleek chrome design connector hoods to complement the aesthetics of style focused commercial and home applications.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 8bit, including stereoscopic 3D, are supported. Cromo HDMI cables are also capable of delivering 32 channel audio and Dolby® True HD.

The latest HDMI specifications are supported for 18G bandwidth capacity in cable lengths up to 5m. Any cables below 5m are classified as high speed, any lengths above 5m are standard cables.

Cromo Line HDMI cables are available in lengths of 0.3m, 0.5m, 1m, 2m, 3m, 5m, 7.5m and 10m.

Technical details

Connectors:

- Connector A: HDMI Type A Male
- Connector B: HDMI Type A Male
- Housing Material: Chrome Plated ABS Plastic
- Connector Plating: 24K Gold 3µm

- Pin Construction: Phosphor Copper
- Pin Plating: 24K Gold 15µm
- Dimensions (approx.) WxDxH: 20x10.6x34mm (0.79x0.42x1.34in)

Cable Construction:

- Length: 0.5m (1.64ft)
- Standard: High Speed HDMI with Ethernet
- Colour: Grey
- Type: Round
- Jack Diameter: 6mm (0.24in)
- Jacket Material: PVC
- Conductor Material: Tin plated copper
- Conductor Gauge: 30AWG
- Shielding: Copper Braid 85%

Specifications:

- Supported Bandwidth: 18 Gbps
- Maximum Resolution: 4096x2160@60Hz 4:4:4 8bit
- Nominal Attenuation: 300kHz-825MHz <5dB, 825MHz-2.475GHz <5dB, 2.475GHz-4.125GHz <12dB, 4.125GHz-5.1GHz <20dB
- Minimum Bend Radius: 60mm (2.36in)
- Operating Temperature: -10°C - 80°C (14°F - 176°F)
- Storage Temperature: -10°C - 80°C (14°F - 176°F)
- ATC Approved: Yes

Miscellaneous:

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: RoHS, REACH, UL, ATC

Purchasing Information:

- No. 37870
- EAN: 4002888378703
- This product is also available in other lengths: 37869 - 0.3m (0.98ft), 37871 - 1m (3.28ft), 37872 - 2m (6.56ft), 37873 - 3m (9.84ft), 37874 - 5m (16.44ft), 37875 - 7.5m (24.61ft), 37876 - 10m (32.81ft)