
### OM3 Multimode Enhanced Pigtail



#### Description

OM3 multimode enhanced pigtails are used to connect high speed networks like gigabit ethernet, fast ethernet and ethernet. The multimode pigtail buffer conforms to IEC, EIA TIA or Telcordia standards. The multimode pigtails are terminated with optimized connector which gives optimum optical performance.

#### Features and Benefits

- SC, LC, ST, FC connectors
- 900 μm tight buffer or easy strip
- Multimode Fiber conforms to ITU-T G.651.1, TIA/EIA
- Available in standard 12 colors as per IEC 60304
- REACH, RoHS & SvHC materials compliant

- Low smoke zero halogen (LSZH) buffer
- OM3 Pigtail is available in standard purple or aqua color
- Different connector performance range for specific application available
- Available in standard and blister packing

#### **Applications**


- Networks including Ethernet, Fast Ethernet and GBE
- Ideal for a wide range of telecom, datacom and process
- Internal inter-connect
- Suitable for repeated handling in patch panels and racks













control applications where ruggedisation is required

### **Specifications**

### **Connector Specification**

OPTICAL PERFORMANCE	MULTIMODE	CONFORMANCE
IL Max/Master (Acceptance)	0.25 dB	IEC 61300-3-4
Ave/Master	0.15 dB	IEC 61300-3-4
Ave/Random	0.20 dB	IEC 61300-3-34

Note: Return Loss > 28dB based on sample data using method IEC 61300-3-6

#### Cable Specification

CHARACTERISTICS	UNITS	SIMPLEX
Crush	N/100 mm	500
Operating Temperature	°C	-20 to 60
Stripping Length - Easy Strip	m	1.5 minimum
Stripping Length - Tight buffer	mm	30 nominal
Nominal buffer Diameter	μm	900 +/- 50
Max Tensile Load	N	6

### Fiber Specification

CHARACTERISTICS	
Attenuation (dB / km)	2.8 @ 850 nm / 0.8 @ 1300 nm
Bandwidth OFL (MHz x km)	1500 @ 850 nm / 500 @ 1300 nm
Bandwidth EMBc (MHz x km)	2000 @ 850 nm

### **Ordering Information**

Code		Cable Type		Fiber Count	Code		Color	Grade	Con	necto r		Code		Unit	Len	ngth
Р3	AA	Easy Strip	1	Single Pigtail	L	6	WHITE	Е	AX	LC	-0000-	Single Pigtail	М	Meters	1	1
	AC	Tight Buffered	В	Pack of 12		Α	PURPLE		DX	SC	-0002-	12 in one Bag			2	2
						С	AQUA		НХ	FC	-0004-	12 in Blister Pack				
						Н	12 Colours		KX	ST						

#### **Legacy Ordering Information**

Connec	Connector End		Fiber Type			ole Length	Cable Construction		
SC	SC	ОМЗ	ОМ3	В	1	1 metre	Tight Buffer		
LC	LC				2	2 metre	-12/1B	Tight Buffer - Pack of 12 colours	











FC	FC		3	3 metre	BP12-TB	Tight Buffer - Blister pack of 12
ST	ST		5	5 metre	EASY	Easy strip
			10	10 metre	E-12/1B	Easy strip - Pack of 12 colours
			XX	Specify	BP12	Easy strip - Blister pack of 12

### **Example Part Number**

	SC	ОМЗ	В	5	-12/1B
--	----	-----	---	---	--------


This part number has created a 5 metre SC OM3 pack of 12 pigtails in different colours.

## Additional Images



















#### **Related Products**



LC Connectors



SC Connector



ST Connectors



FC Connectors



FCP2 Fiber Cleaning Kit for SC/ST/FC/LC



FCP2 Fiber Cleaning Kit for SC/ST/FC/LC/MPO



One-Click® Cleaner D-LC, Duplex LC







