NPCO6UZDB-BK



NPC RJ45 Patch Cord, category 6, U/UTP, LSZH, black

- High-performance patch cords exceeding industry standards supporting NETCONNECT channel specifications
- Standardized transparent, slim-line boots provides consistent patch cord appearance and supports highest density applications
- Colored clips are available to fit the transparent boot, eliminating the need of multiple colors for matching every jacket color
- Colored pull latch tabs are available for easier plug release handling from the modular jack

Product Classification

Regional Availability Asia | EMEA | Latin America

Portfolio NETCONNECT®

Product Type Twisted pair patch cord

Product Series NPC

General Specifications

ANSI/TIA Category 6

Cable TypeU/UTP (unshielded)

Conductor Type Stranded
Interface Feature, connector A Standard
Interface Feature, connector B Standard
Interface, Connector A RJ45 plug
Interface, Connector B RJ45 plug
Jacket Color Black

Pairs, quantity 4
Wiring T568B

,

Dimensions

Cable Assembly Length, metric, minimum 1 m | 3.281 ft

Cable Assembly Length, metric, maximum100 m | 328.084 ftDiameter Over Jacket5.97 mm | 0.235 in

Compatible Conductor Gauge, stranded 24 AWG

Mechanical Specifications

Plug Insertion Life, minimum 750 times

COMMSC PE°

NPCO6UZDB-BK

Environmental Specifications

Operating Temperature $-20 \,^{\circ}\text{C}$ to $+60 \,^{\circ}\text{C}$ (-4 °F to $+140 \,^{\circ}\text{F}$)

Relative Humidity Up to 93%, non-condensing

Environmental Space Low Smoke Zero Halogen (LSZH)

Safety Standard UL 1863

Packaging and Weights

Packaging quantity 1

Included Products

2 8 4 3 0 2 0 - 3

MP-6AU-Boot-59-1 — Integrated Boot and Pair Manager for MP-6AU, size 59, transparent

6 - 2 8 4 3 0 0 7 - 1

MP-6AU-Plug-A-1 — Modular Plug, Category 6A/6, Unshielded, Cond Insulation OD - 0.99mm, 100 pcs