3-1711758-0

MRJ21™ High Speed Cable Assembly, MRJ21-MRJ21, 180°–180°, 1GbE, 24-pair, U/F/UTP, 30 m

- Universal modular copper cabling platform for applications such as Gigabit Ethernet, VoIP and Power over Ethernet
- Increased I/O port density and cleaner cabling schemes compared to RJ45 connectors and cabling
- Robust die cast cable covers provide straight, or 45 deg left/right cable exit for ease of routing

Product Classification

Regional Availability	Asia | Australia/New Zealand | EMEA
Portfolio	CommScope®
Product Type	Copper trunk cable assembly
Product Brand	MRJ21™
Product Series	MRJ21

General Specifications

ANSI/TIA Category	6
Application	Ethernet, 1 GbE
Cable Type	F/UTP (shielded)
Conductor Type	Solid
Construction Type	Stranded
Interface Feature, connector A	Backshell, 180°
Interface Feature, connector B	Backshell, 180°
Interface, Connector A	MRJ21 plug
Interface, Connector B	MRJ21 plug
Jacket Color	White
Pairs, quantity	24
Total Ports, quantity	6

Dimensions

Cord Length	30 m | 98.425 ft
Diameter Over Jacket	16 mm | 0.63 in
Compatible Conductor Gauge, solid	24 AWG

Electrical Specifications

Safety Voltage Rating	150 V

Page 1 of 2

COMMSCOPE®

3-1711758-0

Material Specifications

Conductor Material   Bare copper

Environmental Specifications

Operating Temperature   -40 °C to +70 °C (-40 °F to +158 °F)

Environmental Space   Low Smoke Zero Halogen (LSZH)

Packaging and Weights

Packaging quantity   1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

COMMSCOPE®