5-1711758-0

MRJ21™ High Speed Cable Assembly, MRJ21-MRJ21, 180°-180°, 1GbE, 24-pair, U/F/UTP, 50 m

- Universal modular copper cabling platform for applications such as Gigabit Ethernet, VoIP and Power over Ethernet
- Increased I/O port density and cleaner cabling schemes compared to RJ45 connectors and cabling
- Robust die cast cable covers provide straight, or 45 deg left/right cable exit for ease of routing

Product Classification

| Regional Availability | Asia Australia/New Zealand EMEA |
|-----------------------------------|-------------------------------------|
| Portfolio | CommScope® |
| Product Type | Copper trunk cable assembly |
| Product Brand | MRJ21™ |
| Product Series | MRJ21 |
| General Specifications | |
| ANSI/TIA Category | 6 |
| Application | Ethernet, 1 GbE |
| Cable Type | F/UTP (shielded) |
| Conductor Type | Solid |
| Construction Type | Stranded |
| Interface Feature, connector A | Backshell, 180° |
| Interface Feature, connector B | Backshell, 180° |
| Interface, Connector A | MRJ21 plug |
| Interface, Connector B | MRJ21 plug |
| Jacket Color | White |
| Pairs, quantity | 24 |
| Total Ports, quantity | 6 |
| Dimensions | |
| Cord Length | 50 m 164.042 ft |
| Diameter Over Jacket | 16 mm 0.63 in |
| Compatible Conductor Gauge, solid | 24 AWG |
| Electrical Specifications | |
| Safety Voltage Rating | 150 V |

Page 1 of 2

©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: January 16, 2020



5-1711758-0

Material Specifications

Conductor Material

Bare copper

Environmental Specifications

| Operating Temperature | -40 °C to +70 °C (-40 °F to +158 °F) |
|-----------------------|--------------------------------------|
| Environmental Space | Low Smoke Zero Halogen (LSZH) |

Packaging and Weights

Packaging quantity

Regulatory Compliance/CertificationsAgencyClassificationCHINA-ROHSBelow maximum concentration valueREACH-SVHCCompliant as per SVHC revision on www.commscope.com/ProductComplianceROHSCompliant

1





©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: January 16, 2020

