


NPC06UZDB-WT



NPC RJ45 Patch Cord, category 6, U/UTP, LSZH, white

- High-performance patch cords exceeding industry standards supporting NETCONNECT channel specifications
- Standardized transparent, slim-line boots provides consistent patch cord appearance and supports highest density applications
- Colored clips are available to fit the transparent boot, eliminating the need of multiple colors for matching every jacket color
- Colored pull latch tabs are available for easier plug release handling from the modular jack

Product Classification

Regional Availability	Asia EMEA Latin America
Portfolio	NETCONNECT®
Product Type	Twisted pair patch cord
Product Series	NPC

General Specifications

ANSI/TIA Category	6
Cable Type	U/UTP (unshielded)
Conductor Type	Stranded
Interface Feature, connector A	Standard
Interface Feature, connector B	Standard
Interface, Connector A	RJ45 plug
Interface, Connector B	RJ45 plug
Jacket Color	White
Pairs, quantity	4
Wiring	T568B

Dimensions

Cable Assembly Length, metric, minimum	1 m 3.281 ft
Cable Assembly Length, metric, maximum	100 m 328.084 ft
Diameter Over Jacket	5.97 mm 0.235 in
Compatible Conductor Gauge, stranded	24 AWG

Mechanical Specifications

Plug Insertion Life, minimum	750 times
------------------------------	-----------

NPC06UZDB-WT

Environmental Specifications

Operating Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Relative Humidity	Up to 93%, non-condensing
Environmental Space	Low Smoke Zero Halogen (LSZH)
Safety Standard	UL 1863

Packaging and Weights

Packaging quantity	1
--------------------	---

Included Products

- 2 8 4 3 0 2 0 - 3**
MP-6AU-Boot-59-1 — Integrated Boot and Pair Manager for MP-6AU, size 59, transparent
- 6 - 2 8 4 3 0 0 7 - 1**
MP-6AU-Plug-A-1 — Modular Plug, Category 6A/6, Unshielded, Cond Insulation OD - 0.99mm, 100 pcs
- C C 8 8 4 0 0 1 1 4 4 / B U**
CC6ZH WHT 4/24 SR U/UTP RL BULK — CC6ZH Category 6 U/UTP Cable, low smoke zero halogen, white jacket, 4 pair count, bulk length, reel