

SPAYOIL

Page: 1

Compilation date: 12.07.2016

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SPAYOIL

Product code: 710.400.000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Lubricating oil

1.3. Details of the supplier of the safety data sheet

Company name: ECS AG

Roosstrasse 53 CH-8832 Wollerau

Switzerland

Tel: +41 (0)44 / 787 53 56

Email: gunnar.kleinmann@ecsag.com

1.4. Emergency telephone number

Emergency tel: Schweiz: Schweizerisches Toxikologisches Informationszentrum; +41 44 251 51 51

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Aerosol 1: H222;

Asp. Tox. 1: H304; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin

irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting

effects. May be fatal if swallowed and enters airways.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.
H304: May be fatal if swallowed and enters airways.

Hazard pictograms: GHS02: Flame

GHS09: Environmental
GHS07: Exclamation mark







SPAYOIL

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P337+313: If eye irritation persists: Get medical advice/attention.

P501: Dispose of to.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

KOHLENWASSERSTOFFE, C6, ISOALKANE, <5%N-HEXAN - REACH registered number(s): 01-2119484651-34

EINECS	CAS	PBT / WEL	CLP Classification	Percent
931-254-9	-	-	Flam. Liq. 2: H225; Asp. Tox. 1: H304;	
		Aquatic Chronic 2: H411; Skin Irrit. 2:		
			H315; STOT SE 3: H336	

KOHLENDIOXID

204-696-9	124-38-9	Substance with a Community	Press. Gas: H280	1-5%
		workplace exposure limit.		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Rinse opened eye for severed minutes under running water.

Ingestion: If symptoms persist consult doctor.

Inhalation: In case of unconsciousness place patient stably in side position for transportation.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Causes skin irritation.

Eye contact: Based on available data, the classification criteria are not met.

Ingestion: May be fatal if swallowed and enters airways.Inhalation: Drowsiness or mental confusion may occur.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

SPAYOIL

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: No further relevant information available.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Water spray. Fight Larger fires with water spray or

alcohol resistant foam.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: No further relevant information available.

5.3. Advice for fire-fighters

Advice for fire-fighters: Additional information: Collect contaminated fire fighting water separately. It must not

enter the sewage system.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately.

6.2. Environmental precautions

Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective

authorities in case of seepage into water course or sewage system. Do not allow to

enter sewers/surface or ground water.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Dispose contaminated material as waste according to item 13. Ensure adequate

ventilation.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS. Safe handling: see section 7

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure good ventilation/exhaustion at the workplace. Keep ignition sources away - Do

not smoke. Pressurised container: protect from sunlight and do not expose to

temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Observe official regulations on storing packagings with pressurised containers.

Pressurised container: protect from sunlight and do not expose to temperatures

exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use. Storage class:

2B

SPAYOIL

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

KOHLENDIOXID

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	9100 mg/m3	-	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and

contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact

with the eyes and skin.

Respiratory protection: Not necessary if room is well-ventillated.

Hand protection: Protective gloves. The glove material has be impermeable and resitant to the product /

the substance / the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Nitrile gloves. Recommended thickness of the material: >=0,4mm The selection of the suitable gloves does not only

depend on the materail, but also on further marks of quality and varies from

manufacturer to manufaturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Breakthrough time of the glove material > 8 hours.

Eye protection: Safety glasses.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Pale brown

Odour: Characteristic odour

Solubility in water: Not miscible or difficult to mix.

Viscosity: Not determined.

Boiling point/range°C: Not applicable Melting point/range°C: Undetermined.

Flammability limits %: lower: 1,0 Vol% upper: 7,4 Vol%

Flash point°C: -26°C Autoflammability°C: >200°C

Vapour pressure: at 20°C: 6600hPa

SPAYOIL

Page: 5

Relative density: Not determined.

pH: Not applicable. **VOC g/I:** 37,01%

9.2. Other information

Other information: Product is not selfigniting. Product is not explosive. However, formation of explosive air /

vapour mixtures are possible. Density at 20°C: 0,07g/cm3

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: No further relevant information available.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: No dangerous reactions known.

10.4. Conditions to avoid

Conditions to avoid: No further relevant information available.

10.5. Incompatible materials

Materials to avoid: No further relevant information available.

10.6. Hazardous decomposition products

Haz. decomp. products: No dangerous decompsition products known.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

KOHLENWASSERSTOFFE, C6, ISOALKANE, <5%N-HEXAN

DERMAL	RAT	1H LC50	>3000	mg/kg
GASES	RAT	4H LC50	>20	mg/l
ORAL	RAT	LD50	>5000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Causes skin irritation.

Eye contact: Based on available data, the classification criteria are not met.

Ingestion: May be fatal if swallowed and enters airways.

SPAYOIL

Page: 6

Inhalation: Drowsiness or mental confusion may occur.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

KOHLENWASSERSTOFFE, C6, ISOALKANE, <5%N-HEXAN

Daphnia magna	LC50/48h	3,87	mg/l
Oryzias latipes	LC50/48h	>1	mg/l

12.2. Persistence and degradability

Persistence and degradability: No further relevant information available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No further relevant information available.

12.4. Mobility in soil

Mobility: No further relevant information available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do

not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and

plankton in water bodies. Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

Waste code number: 15 01 10

Disposal of packaging: 15 01 04 metallic packaging Recommendation: Disposal must be made according to

official regulations.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

SPAYOIL

Page: 7

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS AEROSOLS

(KOHLENWASSERSTOFFE, C6, ISOALKANE, <5%N-HEXAN)

14.3. Transport hazard class(es)

Transport class: 2 (5F+Gase)

14.4. Packing group

Packing group: Void

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: Warning: Gases EMS Number: F-D,S-U Stowage Code: SW1, SW22 Segregation Code:

SG69

Tunnel code: D

IMDG seg. group: LQ:1L; EQ E0

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk: not applicable

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Directive 2012/18/EU Named dangerous substances - ANNEX 1 None of the ingredients

is listed. Seveso category:

E2 Hazardous to the Aquatic Environment

P3b Flammable Aerosols Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t. Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t. Regulation (EC) No 1907/2006 ANNEX XVII Conditions of

restriction:28

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

SPAYOIL

Page: 8

H229: Pressurised container: May burst if heated

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.