

Delock HDMI Ethernet Extender by TCP/IP single receiver

Description

This HDMI single receiver by Delock allows in conjunction with the Extender Set Delock 65494 to transmit HDMI signals over a TCP/IP network. The receiver can be connected with a network cable of up to 100 meters.



Specification

- Connectors:
 - 1 x RJ45 jack
 - 1 x HDMI-A 19 pin female
 - 1 x DC 5.5 x 2.1 mm female
- Following TCP/IP standard (Broadcasting)
- M-JPEG decoding up to 1080p @ 60 Hz
- Supported resolutions: 480i / 480p / 576i / 576p / 720p / 1080i / 1080p
- Supports EDID und HDCP
- Video bandwidth up to 165 MHz / 1.65 Gb/s
- Optional: simultaneous operation of multiple receivers
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): ca. 103 x 84 x 25 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 9 mm

System requirements

- Delock HDMI Ethernet Extender set 65494
- One HDMI cable to the HDMI display
- One Cat.5e or Cat.6 network cable
- Switch with VLAN or IGMP Snooping

Package content

- HDMI Extender TCP/IP (receiver)
- External power supply
- User manual

Item no. 65594

EAN: 4043619655946

Country of origin: China

Package: • White Box

Images

