

# Delock DisplayPort 1.2 cable female to female panel-mount 4K 60 Hz 1 m

## Description

This cable by Delock can be used to extend a DisplayPort connection and to connect various devices. The female port can be attached with two screws, e.g. to a slot bracket, a cable duct or an enclosure with the corresponding opening. In this way, it is possible to install a DisplayPort connector in an easily accessible position.



## Specification

- Connectors:
  - 1 x DisplayPort female >
  - 1 x DisplayPort female panel-mount
- DisplayPort 1.2 specification
- Pin 20 is connected (supports 3.3 V)
- Screw type: M3
- Screw distance: 27 mm
- Cable gauge: 28 AWG
- Cable diameter: ca. 7 mm
- Copper conductor
- Triple shielded cable
- Contacts gold-plated
- Transmission of audio and video signals
- Data transfer rate up to 21.6 Gbps
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Supports HDR
- Supports HDCP 1.4 and 2.2
- Colour: black
- Length incl. connectors: ca. 1 m

## System requirements

- A free DisplayPort interface

## Package content

- DisplayPort panel-mount cable
- 2 x screw

## Item no. 87100

EAN: 4043619871001

Country of origin: China

Package: Box

## Images



**General**

Specification:	DisplayPort 1.2
	HDCP 1.4
	HDCP 2.2
	HDR

**Interface**

Connector 1:	1 x DisplayPort male
Connector 2:	1 x DisplayPort female

**Technical characteristics**

Data transfer rate:	21,6 Gb/s
Maximum screen resolution:	3840 x 2160 @ 60 Hz

**Physical characteristics**

Cable diameter:	7 mm
Pin finishing:	gold-plated
Conductor material:	copper
Conductor gauge:	28 AWG
Screw distance:	27 mm
Screw type:	M3
Shielding:	triple
Length:	1 m
Colour:	black