

USB 3.1 Type C Mini Docking Station HDMI/RJ45/PD

No.: 43239



Description

- USB 3.1 Gen1 Type A SuperSpeed port, backwards compatible with USB 2.0
- RJ45 Gigabit Ethernet port with LEDs
- Supports Ultra HD 4k 30Hz for HDMI displays
- USB Type C Power Delivery Input port, 60W
- 2 Year Warranty

With its compact design and featuring all the interfaces needed for a standard workstation, the LINDY USB 3.1 Type C Mini Docking Station uses a single integrated cable to connect to a Notebook to simultaneously provide display, power, gigabit Ethernet and a USB 3.1 SuperSpeed port.

Using DisplayPort Alternate Mode via its USB Type C port the Docking Station enables the connection of a monitor to a compatible notebook via HDMI. Resolutions up to Ultra HD 4K 30Hz are supported.

With support for USB Power Delivery (60W) the Docking Station is able to provide power to a compatible Notebook via its Type C port, eliminating the need for an additional power supply and helping to clear space in your workstation.

The Docking Station's integrated USB 3.1 SuperSpeed port provides up to 5Gbp/s of data transfer. Perfect for your Type A peripherals such as a hard drive, printer or webcam.

Please Note: This product requires DisplayPort Alternate Mode support on the host computer.

Also any interruption of the power supply will cause the USB bus to reset. This is a technical limitation of USB PD 2.0.

Package Contents:

USB 3.1 Type C Mini Docking Station
LINDY Manual

Technical details

Connectors:

- Host Interface: USB 3.1 Gen 1/Thunderbolt 3 with DisplayPort Alternate Mode
- USB Ports:
 - 1 x USB Type C Female for Power Delivery up to 60W
 - 1 x USB 3.1 Gen1 Type A Female
- Video Interface: HDMI v1.4
- Supported Resolutions: Up to Ultra HD 4K 3840x2160p 30Hz

- USB Power Delivery up to 60W (20V 3A Maximum)
- Supports Gigabit Ethernet 10/100/1000Mbps
- Chipsets:
 - USB: VL812
 - Ethernet: RTL8153-VC
 - Power Delivery: VL100
 - HDMI: PS176

Physical Characteristics:

- Dimensions (WxDxH): 8x4x1.5cm
- Weight: 0.04kg
- Operating/Storage Temperature: 0°C - 45°C / -10°C – 70°C
- Humidity: 10 – 85% RH (non condensing)
- Housing: Plastic
- Colour: White