



## USB 3.0 Gigabit Ethernet Converter with Switch

No.: 43123

Connect two computers to a Gigabit network

### Description

- Connects a computer or another LAN device with USB 3.0 Type A port to a Gigabyte Network
- Integrated 2 port switch
- Supports 10/100/1000BASE-T, full and half duplex mode
- USB 3.1 Gen 1 / 3.0 SuperSpeed data transfer rates up to 5Gbps
- 2 year warranty

The Lindy USB 3.0 Ethernet Converter with Switch allows users to conveniently connect two notebook or desktop PCs to a Gigabit Ethernet network via a Type A USB port.

This converter is ideal for notebooks which do not feature wired network connectivity and for locations which lack wireless connectivity or where it is unreliable or slow.

With its small size and lightweight design this USB 3.0 Ethernet Converter is easy and convenient to carry.

The USB 3.0 Ethernet Converter does not require a power supply when connected to the computer via the USB 3.0 interface, however, when the computer is turned off power can be provided through the USB Micro-B port to maintain the network connection.

### Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

## Technical details

### Specifications

- Interface: USB to 2 x RJ45
- Interface Standard: USB 3.1 Gen 1 / 3.0, Gigabit LAN
- Supported Bandwidth: 5Gbps, 10/100/1000Mbps
- Chipset: AX88179
- Compatibility: USB Type A equipped computers
- Power Delivery: -
- Special Features: Allows network connection of multiple computers

### Connectors

- Inputs: 1 x USB Type A (Male)
- Outputs: 2 x RJ45 (Female)
- Power: Bus-powered, USB Micro-B socket

### Physical Properties

- Dimensions WxDxH: 50x73x22mm [1.97x2.87x0.87in]
- (Fixed) Cable Length: 180mm [7.09in]
- Housing Material: Plastic
- Net Weight: 0.05kg [0.11lb]
- Operating Temperature: -20°C - 80°C [-4°F - 158°F]
- Storage Temperature: -20°C - 85°C [-4°F - 185°F]
- Humidity: 0 - 80% RH (non-condensing)
- Power Requirements: 5VDC 1A/2A
- Colour: Black

### Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 155x98x30mm [6.1x3.86x1.18in]
- Gross Weight: 0.118kg [0.26lb]
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH

### Package Contents

- USB 3.0 Ethernet Converter with Switch
- LINDY Driver CD
- LINDY Manual

### Purchasing information

- No.: 43123
- EAN: 4002888431231