



7 Port USB 3.1 Gen 2 Metal Hub

No.: 43275

7 additional USB 3.1 Gen 2 ports - perfect for industrial applications

Description

- Connects 4 Type A and 3 Type C USB 3.1 Gen 2 devices to a Type C port with SuperSpeed+ data rates up to 10Gbps
- Hard-wearing USB Hub - Perfect for industrial applications
- Robust metal housing with high EMC protection and integrated brackets for mounting
- Powered by external power supply or terminal block
- 2 year warranty

The Lindy 7 Port USB 3.1 Gen 2 Metal Hub has been designed to provide reliable performance in demanding operating environments at USB 3.1 Gen 2 speeds up to 10 Gbps. This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this hub is the ideal solution for industrial environments. All Type C sockets of the hub allow the connection of single or dual screw USB 3.1 cables which are compliant with USB-IF Type C locking specification.

Each port features individual short circuit protection - and all 7 USB ports support the Battery Charging specification 1.2 with a total charging power of 40 Watts for all 7 ports. The hub can be powered by the included power supply or the terminal block, ensuring flexible, secure and uninterrupted electricity supplies.

Technical details

Specifications

- USB Standard: USB 3.1 Gen 2
- Supported Bandwidth: 10Gbps
- Chipset: 2x VL820
- Compatibility: USB Type C equipped computers, Thunderbolt 3
- Power Delivery: -
- Special Features: Integrated brackets for mounting; allows connection of USB Type C locking cables; Terminal Block

Connectors

- Inputs: 1 x USB Type C (Female)
- Outputs: 3 x USB Type C (Female), 4 x USB Type A (Female)
- Power: DC screw connector

Physical Properties

- Dimensions WxDxH: 184.5x64.3x20mm (7.26x2.53x0.79in)
- (Fixed) Cable Length: -

- Housing Material: Metal
- Net Weight: 0.3kg (0.66lb)
- Operating Temperature: 0°C - 50°C (32°F -122°F)
- Storage Temperature: -20°C - 60°C (-4°F -140°F)
- Humidity: 90% RH (non-condensing)
- Power Requirements: 16VDC 3A
- Colour: Black

Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 260x180x70mm (10.24x7.09x2.76in)
- Gross Weight: 0.844kg (1.86lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH, California Proposition 65

Package Contents

- 7 Port USB 3.1 Gen 2 Metal Hub
- 0.55m USB 3.1 Gen 2 Dual Screw Type C Male to Male Cable
- Multi-Country Power Supply (EU, UK, US, AUS) with screw type DC connector
- Lindy Manual

Purchasing information

- No.: 43275
- EAN: 4002888432757

© LINDY 2020